RAIL.40S

Rail drilling machine

EUROBOOR FOR PROFESSIONALS BY PROFESSIONALS

Technical data

| | Metric | Imperial |
|------------------------|--------------|------------------------|
| Annular cutting | Ø 12 - 36 mm | Ø 7/16" - 1 7/16" |
| | | |
| Length | 230 mm | 9 1/16" |
| Width | 180 mm | 7 1/16" |
| Height | 495 – 610 mm | 19 1/2" - 24" |
| Stroke | 155 mm | 6 1/8" |
| Weight* | 12 kg | 26.5 lbs |
| Motor power | 1,150 W | 10.5 A |
| Total power | 1,200 W | 10.9 A |
| Speed | 600 rpm | |
| (no load) | | |
| Speed | 380 rpm | |
| (load 1,150 W, 10.5 A) | | |
| Spindle (Weldon) | 19.05 mm | 3/4" |
| Voltage | | 110 - 120 V / 60 Hz |
| | 22 | 0 - 240 V / 50 - 60 Hz |
| | | |

^{*} Without power cord and handles

Features





Euroboor makes every effort to meet quality and integrity requirements. That is why we as an organization are proud of the recognition of some leading organizations worldwide:















Available in 6 different rail adapter versions: S49, S54, TRC68, UIC50, UIC54 and UIC60.